

# DP-22CD4526FWD-IZ

## 2MP Outdoor Dome Network Camera




**DARKFIGHTER**



### Key Features

- 2MP high resolution
- Full HD1080p video, up to 60fps
- Ultra-low light
- Motorized VF lens with Smart Focus
- 120dB WDR
- Up to 40m IR range
- IP66
- Vandal-proof
- Full Smart Feature-set
- Audio/Alarm IO
- Built-in heater (-H)

### Dimensions



DP-22CD4526FWD-IZ	
<b>Camera</b>	
Image sensor	1/1.8" Progressive Scan CMOS
Min. illumination	0.002 Lux @(F1.2,AGC ON), 0 Lux with IR 0.0002 Lux @(F1.4,AGC ON), 0 Lux with IR
Shutter time	1 s to 1/100,000 s
Lens	2.8-12mm @ F1.4, 92°- 32°
Lens mount	Φ14
Angle Adjustment	Pan:0° - 355°, Tilt: 0° - 75°, Rotation: 0° - 355°
Auto-iris	DC drive
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	120dB
<b>Compression standard</b>	
Video compression	H.264 / MJPEG / MPEG 4
H.264 Type	Baseline Profile / Main Profile / High Profile
Video Bit Rate	32 Kbps – 16 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Bit Rate	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)
<b>Image</b>	
Max. Resolution	1920 × 1080
Frame rate	50Hz: 50fps(1920 × 1080) 50fps (1280 × 960), 50fps (1280 × 720) 60Hz: 60fps(1920 × 1080) 60fps (1280 × 960), 60fps (1280 × 720)
Third Stream	Independent with Main Stream and Sub Stream, up to 50Hz: 25fps(1920 × 1080) ; 60Hz: 30fps (1920 × 1080)
BLC	Support, zone optional
Defog	Support
Day/Night Switch	Auto/Schedule/Triggered by Alarm In
ROI	Support
Picture Overlay	24bit BMP format overlay, zone optional
<b>Network</b>	
Network storage	Micro SD/SDHC/SDXC card with ANR (up to 64G), NAS (Support NFS,SMB/CIFS)
Alarm Trigger	Line crossing detection, Intrusion detection, scene change detection, audio exception detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Security	One-key recovery, flash-prevention, three streams, heartbeat, mirror, password protection, video mask, Watermark, IP address filtering, Anonymous access
Standard	ONVIF, PSIA, CGI, ISAPI
Communication Interface	1 RJ45 10M/100M Ethernet interface
<b>Interface</b>	
Audio Input	1-ch 3.5 mm audio interface, Mic in/Line in
Audio Output	1-ch 3.5 mm audio interface
Communication Interface	1 RJ45 10M/100M Ethernet port, 1 RS-485 interface
Alarm Input / Output	1 / 1
Video Output	1Vp-p composite output (75 Ω/BNC)
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 64 GB
Reset Button	Yes
<b>Smart Feature-set</b>	
Behavior Analysis	Line crossing detection, Intrusion detection, Region entrance, Region exiting, Unattended baggage, Object removal
Line Crossing Detection	Cross a pre-defined virtual line
Intrusion Detection	Enter and loiter in a pre-defined virtual region
Region Entrance	Enter a pre-defined virtual region from the outside place
Region Exiting	Exit from a pre-defined virtual region
Unattended Baggage	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
Object Removal	Objects removed from the pre-defined region, such as the exhibits on display.
Exception Detections	Scene change detection, Sudden audio increase/decrease detection, Audio loss detection, Defocus detection
Recognition	Face detection recognition
Statistics	Object Counting (Entrance and Exit object number is accounted and showed on screen in real time)
<b>General</b>	
Protection Level	IP66
Operating conditions	-30 °C – 60 °C (-22 °F – 140 °F), Humidity 95% or less (non-condensing) -H: -40 °C – 60 °C
Power supply	DC12V / AC 24 V± 10%, PoE (802.3af) -H: DC12V/AC24V/PoE(802.3at)
IR Distance	Up to 40m
Power Consumption	Max: 12W -H: 17W
Dimensions	Φ 164.9 × 127 mm(Φ 6.49" × 5")
Weight	2100g (4.62 lbs)