

DP-1204Q-F1/N TURBO HD DVR



Features and Functions

- Connectable to AHD, HD-TVI, network and analog cameras;
- Support DUNLOP protocol for connecting camera over coax;
- Support enabling H.264+ to ensure high video quality with lowered bitrate;
- Provide HDMI, VGA and CVBS outputs, and simultaneous HDMI/VGA output at up to 1920×1080p resolution;
- One-key recording configurable;
- Redundant recording and holiday recording;
- Main stream and sub-stream parameters configurable for simultaneous recording;
- Support channel-zero encoding;
- Support 1080p lite mode enabled to realize the real-time 1080p lite and 720p lite resolution;
- Instant playback for assigned camera in live view mode;
- Up to 4/8-ch synchronous playback at 1080p resolution;
- Playback at up to 256X speed;
- Main stream and sub-stream selectable for local/remote playback;
- Playback by smart search (motion/intrusion/line crossing detection triggered recording);
- Playback by VCA search;
- Customization of tags, searching and playing back by tags;
- Manual VQD (video quality diagnostics);
- Supports locking and unlocking of video files;
- HDD quota and group management;
- One self-adaptive 10M/100Mbps network interface;
- Supports access by EZVIZ Cloud P2P;
- Supports Dunlop DDNS (Dynamic Domain Name System)



Specifications

Model		DP-1204Q-F1/N
Video/Audio input	Video compression	H.264
	Analog video input	4-ch
		BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection
	Supported HD TVI input	1080p/25Hz, 1080p/30Hz, 720p/25Hz, 720p/30Hz, 720P/50Hz, 720p/60Hz
	Supported AHD input	720p/25Hz, 720p/30Hz
	IP video input	1-ch
		Up to 1080p resolution
Audio compression	G.711u	
Audio input/Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)	
Video/Audio output	CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
	HDMI/VGA output	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	Encoding resolution	When 1080p Lite mode not enabled: 1080p(non-real-time)/720p/VGA/WD1/4CIF/CIF; When 1080p Lite mode enabled: 1080p lite/720p lite/720p/VGA/WD1/4CIF/CIF
	Frame rate	Main stream: 1/16 fps to Real time frame rate
		Sub-stream: WD1/4CIF@12fps, CIF/QVGA/QCIF@ real time frame rate
	Video bitrate	32 Kbps to 6 Mbps
	Audio output	1-ch, RCA (Linear, 1KΩ)
	Audio bitrate	64 Kbps
	Dual-stream	Support
	Stream type	Video, Video & Audio
Synchronous playback	4-ch	
Network management	Remote connections	128
	Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Hard disk	SATA	1 SATA interface
	Capacity	Up to 6TB capacity for each disk
External interface	Network interface	1; 10M/100Mbps self-adaptive Ethernet interface
	Serial interface	1; standard RS-485 serial interface, half-duplex
	USB port	2 × USB 2.0
General	Power supply	12 VDC
	Consumption (without hard disks)	≤ 15 W
	Working temperature	-10 °C to +55 °C (14 °F to 131 °F)
	Working humidity	10% to 90%
	Chassis	Standalone 1U chassis
	Dimensions(W × D × H)	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)
Weight(without hard disks)	≤ 2 kg (4.4lb)	