



MODEL		GZS-808PoE-M
Video/Audio input	Analog video input	None
	IP video input	12-ch 8 PoE supported
Video/Audio output	Two-way audio	1-ch, G.722
	Incoming bandwidth	160Mbps
	Recording resolution	1080p/720p/4CIF/2CIF/CIF
	VGA output	1-ch Resolution: 1920×1080 / 60Hz, 1280×1024 / 60Hz, 1280×720 / 60Hz, 1024×768 / 60Hz
	CVBS output	3-ch Aviation plug (1.0 Vp-p, 75 Ω); resolution: PAL: 704 × 576, NTSC: 704 × 480
Decoding	Audio output	3-ch Aviation plug (linear level, 600 Ω)
	Live view	8-ch
Hard disk	Synchronous playback	1-ch
	Type	Two 2.5-inch SATA HDDs / SSDs, external storage expansion supported (reserved)
	Capacity	Up to 2*1TB capacity supported
	Installation	Pluggable
Wireless Network	Protection	3-generation hard disk box
	Backup	Hard disk box, USB interface and eSATA interface supporting data backup
	Dialing	3G (WCDMA), dual SIM card mode reserved
Positioning	Wi-Fi (optional)	802.11 b/g/n supported, 2.4GHz
	GNSS	GPS
External interface	Alarm in	7-ch high/low level signal input; 1-ch pulse signal input; 3mm connector
	Alarm out	2-ch; 3mm connector
	Network interface	1; RJ45; 10M/100M self-adaptive Ethernet interface
	PoE	8; RJ45
	Antenna interface	SMA interfaces: two for 3G (one for reserved), one for Wi-Fi (optional) and one for GPS
	Serial interface	RS-232, RS-485, 3mm connector
	eSATA interface	1
General	USB interface	1 × USB2.0
	EXPSTOR	Connectable to external HDD for storage expansion (reserved)
	SIM card	2, standard SIM card slots (one for reserved)
	Operating system	Linux
	Operating method	IR remote control
	Power supply	Input: +8~ +36VDC; Output: 12VDC/2A, 5VDC/1A
	Consumption	Standby: Max. 0.5W; Full load: Max.20W (without IP camera or hard disk)
	Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
	Working humidity	10%~95%
	Dimensions (W×D×H)	245.8mm×202mm×86.87mm
Weight	Aprox.3.3kg (without hard disk)	