

## DP-12CD1110F-IS



### Key Features

Up to 1.3 megapixel (1280 × 960) resolution

Standard video compression with high compression ratio, ROI (region of interest) encoding

Progressive scan CMOS, capture motion video without incised margin

Support dual stream, and the sub-stream for mobile surveillance

High-performance and long service life infrared LED, Approx. 10 to 30 meters IR range

Two-way audio(-S)

Audio I/O(-S)

IR cut filter with auto switch

PoE (Power over Ethernet)

Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB

Ingress Protection level: IP66

Impact Protection: K10

Other functions: rotate mode, alarm, mirror, reset button, etc

Support intrusion detection, line crossing detection

Support VCA, which is compatible with NVR for the second time of video searching and analysing

### Specification

	Model	DP-12CD1110F-IS
Parameter		1.3 Megapixel CMOS Vandal-proof Network Dome Camera
Camera		
Image Sensor		1/3" Progressive Scan CMOS
Min. Illumination		0.01Lux @ (F1.2, AGC ON), 0 Lux with IR

---

# DUNLOP

By Hikvision Digital Technology

	0.028 Lux @ (F2.0, AGC ON) ,0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	4mm@ F2.0 (2.8mm, 6mm optional)
	Angle of view: 92.5°(2.8mm), 73.1°(4mm) , 46°(6mm)
Lens Mount	M12
Day &Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Angle Adjustment	Pan:0° - 355°, Tilt: 0° - 75°, Rotation: 0-355°
Compression Standard	
Video Compression	H.264/ MJPEG
H.264 Type	Main Profile
Video Bit Rate	32 Kbps – 12 Mbps
Dual Stream	Yes
Audio Compression(-S)	G.711/G.722.1/G.726/MP2L2
Audio Bit Rate(-S)	64Kbps(G.711) /16Kbps(G.722.1)/16Kbps(G.726) /32-128Kbps(MP2L2)
Image	
Max. Resolution	1280 x 960
Frame Rate	50 Hz: 25 fps (1280 × 960), 25 fps (1280 x 720) 60 Hz: 30 fps (1280 × 960), 30 fps (1280 x 720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone optional
ROI	Support
Network	
Network Storage	Local storage: Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB. NAS (Support NFS,SMB/CIFS)
Alarm Trigger	Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
General	One-key reset, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standard	ONVIF, PSIA, CGI, ISAPI
Interface	

# DUNLOP

By Hikvision Digital Technology

Communication Interface	1 RJ45 10M/100M Ethernet interface
Alarm interface	-S: 1 alarm I/O
Audio interface	-S: 1 audio I/O
<b>General</b>	
Operating Conditions	-30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 10% PoE (802.3af)
Power Consumption	Max. 5W
Ingress Protection level	IP66
IR Range	30 meters
Impact Protection	IK10
Dimensions	Φ111 × 82 (4.4" × 3.2")
Weight	500g (1.1 lb)

## Dimensions

